

BeBox Ultra10 312/436 LFP



FEATURES:

- Containerised outdoor mobile system including inverter, air conditioning and fire protection equipment
- Battery inverter and energy management system (EMS)
- Quick & easy installation
- Separate battery and inverter areas for efficient temperature management monitoring
- Cutting edge control and operator interface with 12" display
- High accessibility for user-friendly maintenance



Output Specifications

Nominal Output power (continuous)	kVA	312.5
Peak Output power (5s)	kW	344
Rated voltage (single phase)	V	230
Rated voltage (three phase)	V	400
Frequency	Hz	50
Phase (s)		3
Nominal energy capacity	kWh	436.1
Reference ambient temperature	°C	25

System data

System pass-through capacity	A	850
Operating temperature range	°C	-10.. +50
Degree of protection	IP	54
Noise pressure @1m (LpA)	dB(A)	<70



Inverter

Quantity	n.	5
Rated apparent power	kVA	62.5
Power factor / Range		1 / ±0.1 - ±0.8



Battery specifications

Battery modules quantity	n.	92
Battery (Type)	Li-Ion LFP	
Module capacity	kWh	4.74
Battery rated Voltage	VDC	736
Depth of Discharge (DoD)	%	90
Battery design life	cycles	>5000
Usable energy @ DoD / AC side	kWh	372.9
Total batteries weight	kg	4416

Instruments, controls & connections

Inverter protection Short Circuit	✓
Inverter protection Overload	✓
Inverter protection Over Temperature	✓
Inverter protection Low Battery	✓
System status control panel	✓
Battery condition	✓
Battery main isolator	✓
Remote monitoring device	✓
Automatic generator auto-start signal	✓

Control Panel

DSE M812 PLC HMI:

- Cutting edge control and operator interface with 12" display
- Full power set up visualization from display
- Standard operational modes ISLAND, MICROGRID, GRID TIED
- Input power control enabling function
- Scheduler function included

CONTROL SECTION:

- Emergency push button (outside and to the right of the control section)
- Differential protection with internal switch
- Modular circuit breaker suitably rated with thermal and magnetic overloads for control, input and output power

POWER SECTION

Input Power Connection




- 1x 400A POWERLOCKS 3P+N+T - INPUT 1 (GENSET)
- 1x 400A POWERLOCKS 3P+N+T - INPUT 2 (GRID)
- Auxiliary Input Power plug 16A CEE for Control/UPS

Output Power Connection

- 2x 400A POWERLOCKS 3P+N+T lines
- 1x 125A CEE 3P+N+T

Overall Dimensions

Length	(L) mm	2962
Width	(W) mm	2435
Height	(H) mm	2590
Weight	kg	10500



The information is aligned with the Data file at the time of download.
Printed on 23/03/2026 (ID 195507)

©2026 | PR Industrial S.r.l. – Loc. Il Piano – 53031 Casole d'Elsa (SI) – ITALY. Company subject to the management and coordination of Generac Power Systems Inc. | All rights reserved | Image shown may not reflect actual package. Specifications subject to change without notice